

Technical Data Sheet

TDS 20.01 THIXOP

Product

Thixotropic additive based on a special polymer, which is intended for thickening EPOXIN and PUREXIN products for applications on vertical and inclined surfaces. THIXOP is a highly effective additive for liquids and pastes.

Application

- Epoxies
- Polyurethanes
- Polyesters
- Bitumens
- Putties
- Sealing varnishes
- Floor systems
- Protective coatings

Technical properties

Basis	Polymer		
Density	g/cm ³	0,95	
Fiber length	µm	100	

Packaging

- Bag 1 kg
- Bag 10 kg

Color

- White

Application procedure

THIXOP is mainly intended for the EPOXIN system. However, the application procedure is the same as for all other materials. Mix slowly THIXOP into the already mixed binder (component A + B). Mixing is carried out slowly with constant stirring with a slow-speed mixer (200-300 rpm). The dosage is controlled according to the needs of the applicator (from 1 to 10% by weight per binder) or according to the procedure in the technical data sheet of thickened products (coatings, penetrations, etc.).

Waste disposal

Follow your local waste law. More detailed information can be found in the current Material Safety Data Sheet.

Shelf life

In original unopened containers, dry, at temperatures from +10 ° C to +25 ° C. Do not store in the sun. Shelf life is 12 months from the date of manufacture on the product packaging.

Safety

Do not drink, eat or smoke while working with the product. Wear prescribed personal protective equipment. For more information on safe handling, storage and disposal of chemical products, see the current version of the Material Safety Data Sheet for this product.

Update

Updated

Issued 16.4.2020

The information and data provided are based on our own experience, research and objective testing and are believed to be reliable and accurate. However, the company cannot know the various uses of the product, nor the methods of application

Údaje o zápisu do OR: Zapsáno KS Ostrava, oddíl B, vložka 2951

Den Braven Czech and Slovak a.s.

Adresa: 793 91 Úvalno 353, tel.: 554 648 200, fax: 554 648 205, Česká republika

Bankovní spojení: KB Krnov, č. ú. 19 - 0848810297 / 0100

used, and therefore under no circumstances warrants beyond the scope of this information as to the suitability of the products for a particular use or use procedures. Each user is obliged to make sure that they are suitable for their own tests. For further information please contact our technical department.

Údaje o zápisu do OR: Zapsáno KS Ostrava, oddíl B, vložka 2951

Den Braven Czech and Slovak a.s.

Adresa: 793 91 Úvalno 353, tel.: 554 648 200, fax: 554 648 205, Česká republika

Bankovní spojení: KB Krnov, č. ú. 19 - 0848810297 / 0100